



Product Information:

MULTIVIS ADT FD 5W-30

SYNTHETIC TECHNOLOGY – ENHANCED PROTECTION

(Formerly known as – Multivis F913D 5W-30)

Description

Multivis ADT FD 5W-30 is a synthetic technology engine oil specially formulated to meet the superior performance and fuel efficiency requirements of the latest generation of Ford diesels. Advanced additive technology ensures reduced wear on critical valve-train components in multi-valve engines, including camshafts and hydraulic cam-followers.

Multivis ADT FD 5W-30 provides:

1. Improved fuel economy.
2. Increased engine efficiency and turbo protection.
3. High and low temperature deposit and sludge protection.
4. Low levels of volatility and therefore reduced fuel consumption.
5. Better thermal stability, improved engine cleanliness.

Applications

Recommended for the petrol and diesel engines fitted in passenger car and light commercial vehicles, including turbo and supercharged versions requiring a low viscosity 5W/30 oil of this specification. Designed primarily for use in Ford 2.2 Duratorq engines. This product is backward compatible with units requiring Ford WSS-M2C913-C.

Performance Levels

API SL/CF

ACEA A1/B1, A5/B5

Ford WSS-M2C913-D

STJLR.03.5003

Physical Characteristics

Viscosity @ 100°C, cSt.	10.1
Viscosity @ 40 °C, cSt.	60.0
Viscosity Index	168
Density @ 15.6°C	0.852
Flash Point (Closed) °C	210
TBN, mg/KOH/g	10.0
Pour Point, °C	-36

Figures based on average production values.

Part No.s: MND001, MND005, MND025, MND205

(TDS Multivis ADT FD 5W-30 – 010716 Issue 1)

